

BC800

Power Supply/Battery Enclosure

Altronix BC800 is a UL Recognized NEMA 1 Rated power supply/battery enclosure that can accommodate a wide variety of Altronix power supplies, sub-assemblies, and accessories. Altronix enclosures feature ample knockouts that are suitable for 0.5" or 0.75" conduits.



BC800


BC800 with optional
12VDC/12AH batteries

Specifications

Features

- 16 Gauge steel enclosure
- Ample knockouts accommodating either 0.5" or 0.75" conduits for convenient access
- Includes camlock and two self-tapping screws to secure door

Capacity

- Enclosure accommodates four (4) 12VDC/12AH batteries

Agency Listings

Component Enclosure USR, CNR:
UL Recognized

Physical and Environmental

Dimensions (H x W x D)

Enclosure:

26" x 19" x 6.25" (660.4mm x 482.6mm x 158.75mm)

Shipping:

31" x 23" x 8.25" (787.4mm x 584.2mm x 209.6mm)

Weight (approx.)

Product: 22.6 lb. (10.25 kg)

Shipping: 29.6 lb. (13.43 kg)

Accessories (order separately)



WM5

WM5, WM25, WM100 - Magnetic Cable Tie Mounts

Altronix WM5, WM25, and WM100 are packs of 5, 25 or 100 magnetic cable tie mounts respectively. They accommodate standard zip ties or velcro straps. These are ideal for wire management in our enclosures.




Mounting Magnet

MM4, MM8, MM12, MM24 - Magnetic Mounting Solution

Altronix mounting magnets accommodate screws and nylon standoffs to allow for mounting various boards/ accessories in any metal enclosure or backplane.

Product Position Chart for the Following Models:

Power Supply/Chargers: AL300ULXB, AL400ULXB2, AL600ULXB, AL1012ULXB, AL1024ULXB2, eFlow3NB, eFlow4NB, eFlow6NB, eFlow102NB, eFlow104NB, eFlow15UB, Tango1B, POE75, POE201, POE240, POE360, POE367, OLS75, OLS120, OLS120D2, OLS180, OLS200, OLS250, OLS350 (220VAC Input power supply/chargers are also accommodated)	(A)
Sub-Assemblies: ACM8(CB), ACMS8(CB), ACMS12(CB), LINQ8ACM(CB)	
AL175ULB, AL176ULB, AL201ULB, ACM4(CB), LINQ8PD(CB), MOM5, PD4UL(CB), PD8UL(CB), PD16W(CB), PDS8(CB), PDS16(CB), NetWay5A, NetWay5B, NetWay5BT(Q), NetWay5P(Q), NetWay5ES(Q), VR6, VR10	(B)



Dimensions and Drawing

Dimensions (H x W x D approximate)

26" x 19" x 6.25" (660.4mm x 482.6mm x 158.75mm)

