

RE2**Rack Mount Battery Enclosure**

Altronix RE2 Rack Mount Battery Enclosure accommodates up to four (4) 12VDC/7AH batteries that can be connected in various configurations for either 12VDC or 24VDC applications.



RE2

Specifications**Features**

- 18 Gauge black enclosure
- 2U rack mount chassis for use in standard EIA 19" rack
- Quick connect terminals (wire gauge 14-20 AWG)

Capacity

- Enclosure accommodates up to four (4) 12VDC/7AH batteries

Agency Listings

- UL: UL 294 Access Control Unit Accessory Enclosure.
- cUL: cUL Listed For CSA Standard C22.2 No.205-M1983, Signal Equipment
- CE European Conformity

Physical and Environmental**Dimensions (H x W x D)**

- Enclosure: 3.2" x 19.0" x 8.4" (81.3mm x 482.6mm x 213.6mm)
- Shipping: 20.25" x 12.5" x 7.25" (514.4mm x 317.5mm x 184.2mm)

Weight (approx.)

- Product: 0.4 lb. (4.72 kg)
- Shipping: 12.9 lb. (5.85 kg)

Accessories (order separately)

BT126

BT126 - Rechargeable Battery,

Sealed lead acid (SLA) battery supplies 12VDC/7AH for security, access, surveillance and fire applications.

Dimensions and Drawing

Dimensions (H x W x D approximate)

3.2" x 19.0" x 8.4" (81.3mm x 482.6mm x 213.6mm)

